


TECHNICAL SPECIFICATIONS MODEL: BPG160-32WR-068-MR160 160 SERIES 3/2 WOODRAKE, BN23732



	$\begin{bmatrix} 58\frac{1}{2}"\\ 67\frac{1}{4}"\end{bmatrix}$
$F = = \frac{1}{16}$	
	¥

Motor size	0.61/1.16 in³	10/19 cc
Required pressure	3500 psi	241 bar
Required flow	30/42 gpm	114/159 Lpm
Saw bar length	35/39 in	889/991 mm
Weight	375 lb	170 kg
0		


BATEMAN MANUFACTURING 5 WINSTAR ROAD ORO-MEDONTE, ONTARIO LOL 2LO, CANADA

WWW.BATEMANMANUFACTURING.COM MAIL@BATEMANMANUFACTURING.COM PHONE: (705) 487-5020 FAX: (705) 487-5290

160 SERIES 3/2 WOODRAKE GRAPPLE			
Open	68"	1727 mm	
Area tip to tip	4.7 ft ²	0.44 m²	
Cylinder Bore	3 1/2"	89 mm	
Lock valve on Cylinder	Excl	Excluded	
Cylinder Max. Pressure	3000 psi	207 bar	
Weight (grapple only)	1200 lb	544 kg	

160 SERIES MANIPULATING ROTATOR

Rotation	Unlimited		
Lifting capacity	74200 lb	33657 kg	
Max pressure	3000 psi	207 bar	
Torque at max. pressure	32428 lb-in	3663.9 Nm	
Rotator flow	10 gpm	38 L/min	
Rotation speed	15 r	15 rpm	
Weight	500 lb	227 kg	



化学的复数形式

2021-12-21

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS AND TO IMPROVE OUR PRODUCTS WITHOUT NOTICE OR OBLIGATION ALL SCRAP AND MATERIAL HANDLING GRAPPLES DESIGNED IN ACCORDANCE WITH ASME BTH-1 DESIGN AND STRENGTH REQUIREMENTS